

BACHARACH, INC.
625 ALPHA DR.
PITTSBURGH, PA 15238

EMERGENCY PHONE: (800) 424-9300 (CHEMTREC)
INFORMATION PHONE: (412) 963-2223
FAX: (412) 963-2091

Material Safety Data Sheet

PRODUCT NAME

(Description)

REVISION 2 - MAR/1995

40ppm vol. Hydrogen Sulfide
200ppm vol. Carbon Monoxide
50% LEL (2.5% molar) Methane
10% vol. Oxygen
Balance Nitrogen

TRADE NAME & SYNONYMS

Alarm Check Test Gas

40ppm Hydrogen Sulfide
200ppm vol. Carbon Monoxide
50% LEL (2.5% vol) Methane
10% vol. Oxygen
Balance Nitrogen

CHEMICAL NAME & SYNONYMS

40ppm Hydrogen Sulfide
200ppm vol. Carbon Monoxide
50% LEL (2.5% molar) Methane
10% vol. Oxygen
Balance Nitrogen

FORMULA (minor components)

H₂S, CO, CH₄, O₂

CAS NUMBERS

Hydrogen Sulfide 7783-06-04
Carbon Monoxide 630-08-0
Methane 74-82-8
Oxygen 7782-44-7
Nitrogen 7727-37-9

CHEMICAL FAMILY

Compressed Gas Mixture

Judgements as to the suitability of information herein for purchaser's purposes are necessarily purchaser's responsibility. Therefore although reasonable care has been taken in the preparation of such information, Portagas Inc. extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to purchaser's intended purposes or consequences of its use. Since Portagas Inc. has no control over the use of this product, it assumes no liability for damages or loss of product resulting from proper (or improper) use or application of the product. Data sheets may be changed from time to time. Be sure to consult the latest edition.

Material Safety Data Sheet

HEALTH HAZARD DATA

TIME WEIGHTED AVERAGE (TWA) EXPOSURE LIMITS (ACGIH 1992-93)

The Hydrogen Sulfide component is 10 ppm (mole), with a 15 ppm (mole) STEL

Carbon Monoxide component is 25 ppm (mole),
OSHA 1989: 35 ppm (mole) PEL; Ceiling Value 200 ppm (mole).

Methane is defined as a simple asphyxiant.

The Oxygen concentration found in this mixture is insufficient for supporting life, and in combination with the other components found in this mixture, it is unfit for human respiration.

Nitrogen is defined as a simple asphyxiant.

SYMPTOMS OF EXPOSURE

At low levels (30+/-15 ppm), continuous exposure to Hydrogen Sulfide will typically result in headaches, dizziness or nausea, and cause irritation to the mucous membrane and eye tissue. Higher levels (250+/-50 ppm) can result in respiratory arrest leading to coma or unconsciousness. Exposure to levels greater than 700 ppm for more than 30 minutes have been fatal. Continuous inhalation of low concentrations may cause olfactory fatigue causing a decreased ability to detect its presence by odor.

Carbon Monoxide and Nitrogen are colorless and odorless. Prolonged exposure will produce headaches, and dizziness from their asphyxiant properties.

TOXICOLOGICAL PROPERTIES

Hydrogen Sulfide is toxic by inhalation as well as irritating to the mucous membrane and eye tissue. Continuous inhalation of low concentrations may cause olfactory fatigue causing a decreased ability to detect its presence by odor. Toxicologically Hydrogen Sulfide reacts with enzymes in the blood stream inhibiting respiration, causing pulmonary disorders resulting in collapse or death.

The State of California lists Carbon Monoxide as a compound known to cause developmental reproductive toxicity. Carbon Monoxide complexes with hemoglobin in

Material Safety Data Sheet

TOXICOLOGICAL PROPERTIES (continued)

the blood stream preventing the hemoglobin from transporting Oxygen from the lungs.

In the event of the displacement of air by release of the mixture in an insufficiently ventilated area, asphyxiation may result if the level of oxygen available for breathing drops below 18% by volume, possibly resulting in headache, loss of balance/dizziness, reduction in the ability to perform movements or speak, weakened sense of touch. In any case, some, all or none of these symptoms may manifest, so that there are no definite warning signs.

RECOMMENDED FIRST AID TREATMENT

Prompt medical attention is mandatory in all cases of overexposure to Hydrogen Sulfide and/or Carbon Monoxide.

Rescue personnel should use self contained breathing apparatus (SCBA).

Avoid when possible, the use of equipment that may create a static discharge or provide an ignition source. Relocate the affected person to an uncontaminated area, if breathing has stopped, provide assisted (mouth-to-mouth) respiration, keeping the person warm and calm. Oxygen or a 5% Carbon Dioxide in Oxygen mixture should be administered by a qualified person.

POTENTIALLY HAZARDOUS MIXTURES WITH OTHER CHEMICALS

Hazardous reactions may occur with Hydrogen Sulfide when mixed with concentrated vapors of Nitric Oxide or other strong oxidizers, and vapors of Chlorine, Oxygen Difluoride or Nitrogen Trifluoride.

PHYSICAL DATA

MOLECULAR WEIGHT

28.19

SPECIFIC GRAVITY

0.98 (Air = 1)

VAPOR PRESSURE

@70F, above Critical Temperatures

LIQUID DENSITY AT BOILING POINT

52.36 lb/ft³ average

GAS DENSITY AT STP

0.072 lb/ft³ average

FREEZING TEMPERATURE

-346F

SOLUBILITY IN WATER

Slight

APPEARANCE AND ODOR

Shipped in pressurized compressed gas cylinders (typically 160 -180 psig).

The vapor is colorless with a characteristic H₂S "rotten egg" odor.

Material Safety Data Sheet

FIRE & EXPLOSION HAZARD DATA

FLAMMABLE LIMITS % BY VOLUME

N/A

EXTINGUISHING MEDIA

N/A (Nonflammable gas), use water if involved in a fire.

NFPA 704 NUMBER (HFR)

1 0 0

ELECTRICAL CLASSIFICATION

Nonhazardous

FLASH POINT

N/A

AUTO IGNITION TEMPERATURE

N/A

SPECIAL FIRE FIGHTING PROCEDURES

When the mixture is involved in a fire, Self Contained Breathing Apparatus is required.

UNUSUAL HAZARDS

None

REACTIVITY DATA

STABILITY

Stable

INCOMPATIBILITY

Possibly strong acid or oxidizer vapors

HAZARDOUS DECOMPOSITION PRODUCTS

Oxides of Sulfur

HAZARDOUS POLYMERIZATION PRODUCTS

None

CONDITIONS TO AVOID

N/A

ACTIONS TO BE TAKEN IN THE EVENT OF AN UNINTENDED RELEASE (LEAK)

FOR EMERGENCIES INVOLVING THIS PRODUCT CALL INFOTRAC (800)535-5053

Evacuate all personnel from the affected area. Use appropriate protective equipment. Shut off flow of gas, and purge lines with an inert gas. Switch off non-essential electrical equipment.

WASTE DISPOSAL METHODS

Do not attempt to dispose of any unused quantities of product or their containers without contacting Portagas for instructions.

Material Safety Data Sheet

PERSONAL PROTECTION INFORMATION

RESPIRATORY/VENTILATION

Self Contained Breathing Apparatus/Hood with forced ventilation to prevent accumulation and exposure to the TLV of Carbon Monoxide and Hydrogen Sulfide, and contribute to LEL conditions, and an Oxygen deficient atmosphere.

GLOVES

Rubber (neoprene, butyl, poly)

EYES AND OTHER

Safety goggles or glasses only, contact lenses are not recommended
15 minute shower/eyewash, steel toed/metatarsal protection shoes.

SPECIAL SAFETY AND REGULATORY CONSIDERATIONS

LABELING	DOT Shipping name:	Compressed Gases, n.o.s.
	Tech. Description:	(Oxygen, Nitrogen)
	Identification No.:	UN 1956
	Hazard Class, Div.:	Nonflammable Gas, 2.2

HANDLING

Use only in well ventilated areas. The cylinder should be secured with a chain, strap on its side or by use of a stand when connected to a regulator. Do not drag, drop or roll the cylinder. Use both hands when carrying the cylinder. Do not heat the cylinder. One-way check valves in the use line are recommended to prevent backflow. Systems should be cleaned "for Oxygen service" before first use.

STORAGE

Protect the cylinders from physical damage. Store the cylinders in a cool (<130F), dry, ventilated, posted "no smoking or open flames" area constructed of non-combustible materials, and away from aisles and other traffic areas. Keep full cylinders separated from empties. Rotate stock first-in, first-out (FIFO).

PACKAGING

Use the cylinders as provided, with the recommended regulator. Do not attempt to refill the cylinder or transfill the product from one container to another.

OTHER PRECAUTIONS

Conduct monitoring of gas exposure to personnel, do not rely on odor as a way to detect the presence of gas.